

INTRODUCTION SCHEDULE

Consumer launch

16th March 2016

EL-SKYPORT TRANSMITTER PLUS

The EL-Skyport transmitter Plus offers simplicity, durability and reliability. Powered by 2.4 Ghz bandwidth, the transmitter enables remote control – on all RX, ELC and ELB units – and triggering capabilities over 16 frequency channels of 4 groups per channel with the range extended to up to 200 m (656').

FEATURES

- Trigger reliably and adjust flash power up to 200 m (656 feet) away.
- Optimize reception by rotating the transmitter.
- 16 different channels (8 in normal mode and 8 in speed mode) are available - 6 for legacy units and 10 for newer units such as ELC Pro HD and ELB 400.
- The flash power per group can be quickly increased or decreased.
- Runs on AA batteries, available everywhere.
- Simple to use. All functionalities can be easily adjusted.
- Durable with robust mechanics thanks to its Swiss design.



EL-Skyport transmitter Plus
19368

Date **15.01.16**

 Bulletin # **08**

SPECIFICATIONS

Frequency Band	2.4 GHz
Channels	16; (8 in Normal mode – green / 8 in Speed mode – red)
Groups	All and 4: 1, 2, 3, 4
Flash synchronization	Normal: limited to the native X-sync of your camera Speed: for digital medium-format cameras
Range	Up to 200m (656') for triggering
Connection	Foot for camera hotshoe 2.5 mm sync socket
Power source	2x AA batteries
Indicators and Controls	Display Group and frequency channel Buttons On top: group selection, synchronization mode, channel selection, power down, power up and test. On side: on/off.
Compatibility	Channels 1, 3 and 7 are compatible with all enabled EL-Skyport units. Channels 1, 3, 7, 9, 12, 15, 18 and 20 are only compatible with ELC Pro HD and ELB 400.
Dimensions	94.9 x 49.9 x 38.3 mm (3.7" x 2" x 1.5")
Weight	68 g (0.14 lbs.) without batteries

IN THE BOX

- 1x EL-Skyport transmitter Plus
- 1x 2.5 mm sync cord to PC
- 1x Wrist strap
- 1x 2-year warranty