

INTRODUCTION SCHEDULE

Consumer launch

16th March 2016

EL-SKYPORT RECEIVER PLUS

The EL-Skyport receiver Plus offers simplicity, durability and reliability. Powered by 2.4 Ghz bandwidth, the receiver enables speedlights and other flash brands to be triggered by the EL-Skyport system over 16 frequency channels of 4 groups per channel with the range extended to up to 200 m (656').

FEATURES

- Trigger reliably and adjust flash power up to 200 m (656 feet) away.
- Hotshoe to securely attach speedlights.
- 16 different channels (8 in normal mode and 8 in speed mode) are available.
- Runs on AA batteries, available everywhere.
- Simple to use. All functionalities can be easily adjusted.
- Durable with robust mechanics thanks to its Swiss design.
- Micro-usb socket for firmware updates.



EL-Skyport receiver Plus
19369

Date **15.01.16**

 Bulletin # **09**

SPECIFICATIONS

Frequency Band	2.4 GHz
Channels	16; (8 in Normal mode – green / 8 in Speed mode – red)
Groups	4: 1, 2, 3, 4
Flash synchronization	Normal: limited to the native X-sync of your camera Speed: for digital medium-format cameras
Range	Up to 200m (656') for triggering
Connection	Foot for camera hotshoe 3.5 mm sync socket Micro-usb for firmware updates
Power source	2x AA batteries
Indicators and Controls	Display Group and frequency channel Buttons On left side: channel selection and synchronization mode. On right side: on/off and group selection.
Compatibility	Channels 1, 3 and 7 are only compatible with the previous EL-Skyport transmitter and EL-Skyport transmitter Speed. Channels 1, 3, 7, 9, 12, 15, 18 and 20 are compatible with the EL-Skyport transmitter Plus and EL-Skyport transmitter Plus HS.
Dimensions	93.6 x 49.5 x 41.6 mm (3.7" x 2" x 1.6")
Weight	76 g (0.17 lbs.) without batteries

IN THE BOX

- 1x EL-Skyport receiver Plus
- 1x 3.5 mm to 3.5 mm sync cord
- 1x 3.5 mm to 6.35 mm adapter
- 1x Wrist strap
- 1x 2-year warranty