

INTRODUCTION SCHEDULE

Consumer launch

16th March 2016

BRX 250/250 UMBRELLA TO GO

The BRX compact flash units are a further evolution of the features and quality that are Elinchrom. The concept is simple: control, power, speed and versatility. With many programmable features and the EL-Skyport remote system, the BRX enables photographers the greatest freedom to express their individuality. The BRX series deliver the quality of performance needed for a modern workflow. They are perfect for portraiture, product and architectural photography.

This set includes the latest EL-Skyport transmitter Plus. A strong and robust design which enables photographer to simply trigger and adjust flash power up to 200 m (656 feet) away, optimize reception by its swivel functionality and is powered by AA batteries.

**BRX 250/250 Umbrella To Go**

20748.2

FEATURES

- Skyport delivers the most comprehensive synchronisation and control, and it's unique to the whole Elinchrom system. Your creative edge in lighting.
- Super short flash durations with our bespoke twin electrode A(Action) flashtube.
- Intelligent pre-flash detector system enables the full use of BRX 250 / 500 with speedlights.
- High capacity intelligent fan cooling offers higher work capacity.
- Independent modelling lamp control.
- Visual Flash Confirmation option. The modelling lamp switches off/on to confirm the flash has been triggered.
- Rigid chassis enables the largest accessories to be used.
- Centred 7 mm umbrella shaft enables also the use of the unique Elinchrom Deflector set.
- Stand bracket with additional umbrella fitting for larger umbrella shafts.
- User replaceable plug-in flashtube.
- Multi-voltage auto-detection: 90-270 V (excluding modelling lamp).

Date **15.01.16**

Bulletin # **04**

SPECIFICATIONS

Energy (Ws/J)	250
F-Stop (1m, 100 ISO, reflector 48°)	45.8
Power range Ws	5
Flash duration t0.5 in s.	Max. power: 1/1558
Recycling 230 V in s.	0.29 – 0.73
Recycling 110 V in s.	0.27 – 1.02
Colour temperature in K°	5500
Auto power dumping	Yes
Power stability	+/- 0.5%
Voltage	Multivoltage 90 – 265 V
Modelling lamp mode	Free, proportional, VFC: -0.5 – -2.0 f-stop
Modelling lamp 230 V	100 W / E 27 - 23002
Modelling lamp 110 V	100 W / E 27 - 23006
Flashtube	S-Type, omega plug-in, user replaceable - 24009
EL-Skyport	Built-in transceiver, 8 frequency channels and 4 groups
Sync voltage	5V
Sync socket	3.5 mm
Fan cooled	Yes
Umbrella fitting	Centered 7mm and additional 8mm bracket on the tilt head
Max. power consumption (230 V / 50 Hz) during charge	380 W
Max. power consumption (115 V / 60 Hz)	270 W

SET CONFIGURATION

- 2x BRX 250; incl. 100 W lamp, protective cap, sync cord and mains cable
- 2x Umbrella wide reflector 90° 16 cm
- 1x Eco silver umbrella 85 cm
- 1x Eco translucent umbrella 85 cm
- 1x EL-Skyport transmitter Plus
- 1x Translucent deflector
- 1x Tripod set 2 (2x 88 – 235 cm with bag)
- 1x Tube case for D-Lite 2/4
- 1x 2-year warranty