

INTRODUCTION SCHEDULE

Consumer launch

16th March 2016

D-LITE RX ONE/ONE SOFTBOX TO GO

Delivering approximately twice the power of speedlights, the D-Lite RX ONE is a small but robust compact flash from Elinchrom. The versatility of the Elinchrom system remains in its accessory range: where it is difficult to change the hard nature that characterizes speedlights, Elinchrom has some of the best accessories allowing photographers to change the nature of their light, to suit their style. Used on location, the D-Lite RX ONE is the perfect creative companion to an existing Speedlight system, making use of the built-in intelligent slave cell to offer perfect flash synchronization.

This set includes the latest EL-Skyport transmitter Plus. A strong and robust design which enables photographer to simply trigger and adjust flash power up to 200 m (656 feet) away, optimize reception by its swivel functionality and is powered by AA batteries.



D-Lite RX ONE/ONE Softbox To Go
20847.2

FEATURES

- 100 Ws down to 6 Ws power range, perfect for small environments and shallow depth of focus.
- Skyport delivers the most comprehensive synchronization and control, and it's unique to the whole Elinchrom system. Your creative edge in lighting.
- Intelligent pre-flash detector system enables the full use of D-Lite RX's with speedlights.
- Very short flash durations to offer sharper images
- Exceptional colour balance across the power range.
- Temperature controlled cooling fan.
- The accessory bayonet accepts the complete range of light modifiers.
- Centred 7 mm umbrella shaft enables also the use of the unique Elinchrom Deflector set.
- Stand bracket with additional umbrella fitting for larger umbrella shafts.

Date **15.01.16**

 Bulletin # **01**

SPECIFICATIONS

Energy (Ws/J)	100
F-Stop (1m, 100 ISO, reflector 48°)	32.4
Power range Ws	5
Flash duration t0.5 in s.	Max. power: 1/2200
Recycling 230 V in s.	0.44 – 1.5
Recycling 110 V in s.	0.45 – 2.1
Colour temperature in K°	5500
Auto power dumping	Yes
Power stability	+/- 0.5%
Voltage	Multivoltage 90 – 265 V
Modelling lamp mode	Free, proportional, VFC: -0.5 - -2.0 f-stop
Modelling lamp 230 V	100 W / E 27 - 23002
Modelling lamp 110 V	100 W / E 27 - 23006
Flashtube	S-Type, omega plug-in, user replaceable - 24009
EL-Skyport	Built-in transceiver, 8 frequency channels and 4 groups
Sync voltage	5V
Sync socket	3.5 mm
Fan cooled	Yes
Umbrella fitting	Centered 7mm and additional 8mm bracket on the tilt head
Max. power consumption (230 V / 50 Hz) during charge	140 W
Max. power consumption (115 V / 60 Hz)	170 W

SET CONFIGURATION

- 2x D-Lite RX ONE; incl. 100 W lamp, protective cap, sync cord and mains cable
- 1x Portalite Square 66 cm
- 1x Portalite Octa 56 cm
- 1x Translucent deflector
- 1x EL-Skyport transmitter Plus
- 1x Tripod set 2 (2x 88 – 235 cm with bag)
- 1x Tube case for D-Lite 2/4
- 1x 2-year warranty